

**Document Analysis Method to Detect BW/Color Areas and
Corresponding Scanning Device**

Field of the Invention

- 5 The present invention relates to a document analysis method and, more particularly, to a document analysis method to detect BW/color areas.

Moreover, the invention relates to a scanning device to acquire documents.

- 10 Finally, the invention relates to a method for acquiring a document based on the analysis of the content of the document itself.

Background of the Invention

- 15 As is well known in the technical field of image processing, during its life an image is processed by a plurality of electronic devices, that create, acquire, display store, read and write the image itself.

- The image data processing device, and the corresponding
20 processing method deal with an image acquired by means of an image acquisition device, for example a scanner.

The image data so obtained are usually organized into a raster of pixels, each pixels providing an elementary image information.

- 25 In other words, images are, at the most basic level, arrays of digital values, where a value is a collection of numbers describing the attributes of a pixel in the image. For example, in bitmaps, the above mentioned values are single binary digits.

Often, these numbers are fixed-point representation of a range of real number; for example, the integers 0 through 255 are often used to represent the numbers from 0.0 to 1.0. Often too, these numbers represent the intensity at a point of the image (gray scale) or the intensity of one color component at that point.

An important distinction has to be made in the images to be processed between achromatic and colored images.

In fact, achromatic light has only one attribute, which is the quantity of light. This attribute can be discussed in the physic sense of energy, in which case the terms intensity and luminance are used, or in the psychological sense of perceived intensity, in which case the term brightness is used.

It is useful to associate a scale with different intensity levels, for instance defining 0 as black and 1 as white; intensity levels between 0 and 1 represent different levels of grays.

The visual sensations caused by colored light are much more richer than those caused by achromatic light. Discussion on color perception usually involves three quantities, known as hue, saturation and lightness.

1. Hue distinguishes among colors such as red, green, purple and yellow.
2. Saturation refers to how far a color is from a gray of equal intensity. Red is highly saturated; pink is relatively unsaturated; royal blue is highly saturated; sky blue is relatively unsaturated. Pastel colors are relatively unsaturated; unsaturated colors include more white light than do the vivid, saturated colors.

3. Lightness embodies the achromatic notion of perceived intensity of a reflecting object.

A fourth term, brightness, is used instead of lightness to refer to the perceived intensity of a self-luminous object (i.e. an object emitting rather than reflecting light), such as a light bulb, the sun or a CRT.

5 The above mentioned features of colors seem to be subjective: they depend on human observers' judgment. In reality, the branch of physics known as colorimetry provides for an objective and quantitative way of specifying colors, which can be correlated to the above
10 perceptual classification.

A color can be represented by means of its dominant wavelength, which corresponds to the perceptual notion of hue; excitation purity corresponds to the saturation of the color; luminance is the amount or intensity of
15 light. The excitation purity of a colored light is the proportion of pure light of the dominant wavelength and of white light needed to define the color.

A completely pure color is 100 % saturated and thus contains no white light, whereas mixtures of a pure
20 color and white light have saturations somewhere between 0 and 100 %. White light and hence gray are 0 % saturated, contains no color of any dominant wavelength.

Furthermore, light is fundamentally electromagnetic
25 energy in the 400-700 nm wavelength part of the spectrum, which is perceived as the colors from violet through indigo, blue, green, yellow and orange to red. The amount of energy present at each wavelength is represented by a spectral energy distribution $P(\lambda)$, as
30 shown in figure 1.

The visual effect of any spectral distribution can be described by means of three values, i.e. the dominant wavelength, the excitation purity, and the luminance. Figure 2 shows the spectral distribution of figure 1,

illustrating such three value. In particular, it should be noted that at the dominant wavelength there is a spike of energy of level e_2 . White light, the uniform distribution of energy level e_1 is also present.

- 5 The excitation purity depends on the relation between e_1 and e_2 : when $e_1=e_2$, excitation purity is 0 %; when $e_1=0$, excitation purity is 100 %.

Luminance, which is proportional to the integral of the area under such curve, depends on both e_1 and e_2 .

- 10 A color model is a specification of a 3D color coordinate system and a visible subset in the coordinate system within which all colors in a particular range lie. For instance, the RGB (red, green, blue) color model is the unit cube subset of a
15 3D Cartesian coordinate system, as shown in figure 3.

- More specifically, three hardware-oriented color models are RGB, used with color CRT monitors, YIQ, i.e. the broadcast TV color system that is a re-coding of RGB transmission efficiency and for downward compatibility
20 with black and white television and CMY (cyan, magenta, yellow) for some color-printing devices. Unfortunately none of these models are particularly easy to use because they do not relate directly to intuitive color notions of hue, saturation, and brightness. Therefore,
25 another class of models has been developed with ease of use as a goal, such as the HSV (hue, saturation, value) - sometimes called HSB (hue, saturation, brightness), HLS (hue, lightness, saturation) and HVC (hue, value, chroma) models.
- 30 With each model is also given a means of converting to some other specification.

As stated above, the RGB color model used in color CRT monitors and color raster graphics employs a Cartesian

coordinate system. The RGB primaries are additive primaries; that is the individual contributions of each primary are added together to yield the result. The main diagonal of the cube, with equal amounts of each primary, represents the gray levels: black is (0,0,0);
5 white is (1,1,1).

Following such gray line implies the change of the three Cartesian value R, G and B at the same time, as shown with a point-dotted line in figure 4A; this
10 situation weights the computational charge of the image processing steps requiring the individuation of gray regions.

The RGB model is hardware-oriented. By contrast HSV (as well as HSB or HLC) model is user-oriented, being based
15 on the intuitive appeal of the artist's tint, shade, and tone. The coordinate system is cylindrical, as shown in figure 4B.

The HSV model (like the HLC model) is easy to use. The grays all have $S=0$ and they can be removed from an
20 image data raster by means of a cylindrical filter in proximity of the V axes, as shown in figure 5; moreover, the maximally saturated hues are at $S=1$, $L=0.5$.

The HLS color model is a reduced model obtained from
25 the HSV cylindrical model, as shown in figure 6; the reduction of the color space is due to the fact that some colors cannot be saturated. Such space subset is defined is a hexcone or six-sided pyramid, as shown in figure 7. The top of the hexcone corresponds to $V=1$
30 which contains the relatively bright colors. The colors of the $V=1$ plane are not all of the same perceived brightness however.

Hue or H, is measured by the angle around the vertical axis with red at 0° green at 120° and so on (see figure

7), Complementary colors in the HSV hexcone are 180° opposite one another. The value of S is a ratio ranging from 0 on the center line (V axis) to 1 on the triangular sides of the hexcone.

- 5 The hexcone is one unit high in V, with the apex at the origin. The point at the apex is black and has a V coordinate of 0. At this point, the values of H and S are irrelevant. The point $S=0, V=1$ is white. Intermediate values of V or $S=0$ (on the center line)
 10 are the grays. It is therefore immediately apparent the simplicity of use of the HSV or equivalent color space in order to obtain the gray regions.

Adding a white pigment corresponds to decreasing S (without changing V). Shades are created by keeping $S=1$
 15 and decreasing V. Tones are created by decreasing both S and V. Of course, changing H corresponds to selecting the pure pigment with which to start. Thus, H, S, and V correspond to concepts from the perceptive color system.

- 20 The top of the HSV hexcone corresponds to the projection seen by looking along the principal diagonal of the RGB color cube from white toward black, as shown in figure 8.

In figure 9 is shown the HLS color model, which is
 25 defined in a double-hexcone subset of the cylindrical space. Hue is the angle around the vertical axis of the double hexcone, with red at 0° . The colors occur around the perimeter: red, yellow, green, cyan, blue and magenta. The HLS space can be considered as a
 30 deformation of HSV space, in which white is pulled upward to form the upper hexcone from the $V=1$ plane. As with the single-hexcone model, the complement of any hue is located 180° farther around the double hexcone, and saturation is measured radially from the vertical
 35 axis from 0 on the axis to 1 on the surface. Lightness

is 0 for black (at the lower tip of the double hexcone)
to 1 for white (at the upper tip).

Many hardware and software packages are currently
available in the technical field of the electronic
5 image processing which provide for image data
processing methods and corresponding devices. However,
it should be noted that only few, if any, operate in
both the personal computer/work station field as well
as in the embedded devices field.

10 In fact, the embedded devices have a plurality of needs
which turn into tight limitations for the image
processing devices themselves. Particularly, the image
processing in an embedded environment seeks:

- to reduce the size of the image data in order to
15 limit the memory area employed by the image data
processing devices;

- to increase the amount of any text portion
comprised in a document that can be OCR'able, i.e. it
should be possible to acquire and understand such
20 portion by means of an Optical Characters Recognitor
(OCR);

- to get as final result of the image data
processing device an image viewable and printable,
which is close to the original acquired image.

25 Known document analysis that tried to fit the above
requirements have the problem of being computationally
very heavy and not suited for embedded applications
where processing power and memory requirements are
stringent and important.

30 So, even if these solutions may perform an acceptable
analysis of the document, they are not applicable in an
embedded environment.

The main purpose of the known document analysis is the extraction of features and the classification of text and images in the analyzed documents. Examples of analysis used in this technical field are known from the publication "Document Image Analysis" to L. O'Gorman and R. Kasturi, IEEE Computer Society Press, which is a collection of all the most relevant papers regarding document analysis.

All the known approaches deal with the recognition of different types of areas on a page. The areas are normally classified into regions of text, photo and line art. The page is then divided into these different areas (normally in a mutually exclusive way) and each is treated in a different way. In other terms, the known document analysis deal with understanding the "type" of information that is on the page.

These solutions tend to sub-divide the page into mutually exclusive regions that contain different type of information.

Other known devices deal with decomposed documents, i.e. documents translated into a plurality of elementary image information called pixels. Such devices provide a treatment of the decomposed document as a whole, or at least are able to reconstruct the information they need only reprocessing the input document format.

An illustrative and not limiting example is a BW fax machine. If such device can deal only with BW data and the document contains a mixture of sparse color and BW data, the fax machine image processing device must be able to reconstruct a single BW page from the pieces of the decomposed original document.

A known way to comply with the embedded environment requirements leads to peripheral devices that support

only the specified features of a particular product;
that is how cost and performance are satisfied.

However, none of the known solutions deals with the
problem of maintaining the original appearance of the
5 document, and therefore no accent is posed on the
recognition of the color itself on the document and
what can be done once this color content is known.

One object of the present invention is that of
providing a dual path distinction method for two
10 different layers, i.e. the BW and color layer,
identifying the features used to classify as colorful
or not a certain group of pixel of a raster image.

The reason for doing this can be explained in the
following way. As an example, in a document as a
15 magazine article, there are areas of color, for example
photographs and colored text and highlighted areas
which include bright colors and which a user would like
to retain as colors. There are also areas, typically
backgrounds areas which are either very light or dark,
20 that even if one could argue that they have a color
content, can be equally be well represented with only
two colors, i.e. black and white.

Moreover, the color information content of background
area, even if not negligible, could be of no interest
25 with respect to the BW content. This is the case of the
so-called "business text": the information content of
the image data is superimposed to a color background
content which can be ignored, without losing any
useful information.

30 After the separation between these areas, the data in
each area could be processed differently: color data
could be compressed in a lossy fashion, whereas the BW
data could be binarized, and the user would not see a
big difference in the quality of the document.

Summary of the Invention

The solution idea behind this invention is that of providing a dual path distinction method which could create a BW and a color layer starting from a single
5 input data sheet.

According to this solution idea, the invention relates to a document analysis method using BW/color areas detection as defined in the enclosed claim 1.

Moreover, the invention relates to a scanning device,
10 as defined in the enclosed claim 9.

Finally, the invention relates to a method for acquiring a document based on the analysis of the content of the document itself, as defined in the enclosed claim 15.

15 The features and advantages of the BW/color document analysis method and layers creator device according to the invention will be appreciated by the following description of a preferred embodiment given by way of non-limiting examples with reference to the annexed
20 drawings.

Brief Description of the Drawings

Figure 1 shows an example of a spectral energy distribution of a color;

Figure 2 shows the spectral distribution of figure 1,
25 illustrating dominant wavelength, excitation purity and luminance.

Figure 3 shows the 3D Cartesian representation of the RGB color space, with the fundamental colors;

Figure 4A shows the RGB color space of figure 3 and the

gray line within;

Figure 4B shows the cylindrical representation of the HSV/HLC color space;

5 Figure 5 shows a gray filter for the HSV/HLC color space;

Figure 6 shows the HLS color space;

Figure 7 shows the single-hexcone representation of HSV color space;

Figure 8 shows a section of figure 7;

10 Figure 9 shows the double-hexcone representation of the HSV color space;

Figure 10 shows schematically a document analysis method according to the present invention;

15 Figure 11A shows schematically a dual path layer creator implementing such method according to the present invention;

Figure 11B shows more particularly the dual path layer creator of figure 11A.

20 Figure 12 shows resulting layers from the dual path layer creator of figure 11A.

Figures 13A, 13B and 13C show a first atomic operation used in the method according to the present invention and its implementation;

25 Figure 14 shows a particular result for the atomic operation of figures 13A, 13B and 13C;

Figure 15 shows another example of atomic operation used in the method according to the present invention;

Figure 16 shows another example of atomic operation

used in the method according to the present invention;

Figure 17 shows more particularly a PDF application of the method according to the present invention.

Detailed Description of the Invention

5 The basic idea underlying present application is that of processing a document in order to provide distinct BW and color layers. Starting from a color page acquired with a scanner capable to deliver color data, the first step is to understand where there is a color
10 on the color page. For this purpose such method uses colorfulness and region groupings for document analysis.

In particular, the document analysis method according to the present invention comprises the following steps:

- 15 1. Getting a color image input data, for example a pixels raster format.
2. Calculating and extracting from the input data the colorfulness of each pixel.
3. Creating a first and a second output layers
20 corresponding to the BW and color pixels respectively.
4. Applying a first set of atomic operations to the BW layer and a second different set of atomic operations to the color layer.
5. Combining the BW and color layers in order to
25 obtain a desired format for the output data.

The purpose of such document analysis method is that of distinguish between text and image; so, the method according to the present invention comprises a first path BW PATH that detects the BW pixels in order to
30 assemble a first layer TEXT containing the portion of text comprised in the input data and a second path

COLOR PATH that detects the color pixels in order to assemble a second layer IMAGE containing the portion of image comprised in the input data.

In figure 10, the method according to the present invention is shown in terms of pipelines, i.e. in term of "paths" of atomic operations to be performed on the input data in order to obtain a particular output format. More particularly, figure 10 shows the two different output representation, TEXT and IMAGE, obtained by means of said first and second data paths, BW PATH and COLOR PATH respectively.

The pipelines or paths define the sequence of atomic operations to be performed on the input image data. Such atomic operations, which are individually known in the field of image data processing, can be grouped together to generate a plurality of IP (Image Processing) tools.

In order to obtain the BW/color layer distinction according to the above method, may be used the following IP tools:

- a transformation of an image pixel from the RGB format to another image space format, for example the HLS (or HLN, for hue, lightness, chroma indicator N) format;
- a grouping function that associates elementary information in order to obtain an unique information group to be processed, as the blobbing technique;
- a down sampling function;
- a thresholding function;
- an AND/OR and other data extraction function;
- compression functions (in particular, the G4 or

JPEG compression method).

Figure 11A shows a dual path layer creator 1, receiving an input data 2 and outputting a first 3 and a second layer 4 of organized output data.

- 5 The input data 2 are in some color format, for e.g., but is not limited to, the RGB format, and they are organized under the form of color pixels raster. It is possible obtaining such data format by means, for example, of a scanner.
- 10 As an example, from a 300dpi 24bpp (bit per pixels) color input image, the dual path layer creator 1 outputs a 300dpi 8bpp [bottom layer] representation of the input data, as well as a 150dpi 24bpp color representation [top layer]. The effect of this is that
- 15 instead of having to process the 300dpi, 24bpp data of 24Mbyte, only 300dpi 8bpp = 8Mbyte and 150dpi, 24bpp = 6Mbyte of data have to be processed, the sum of 14 Mbyte being much less than the original 24Mbyte.

- Advantageously, according to the present invention, the
- 20 dual path layer creator 1 produces the two document layers 3 and 4 simultaneously.

- Particularly, such layers 3 and 4 have a different resolution, as shown in figure 12. As an example, a resolution of 150dpi is used when the color information
- 25 of the image input data is needed, e.g. in case of a graphic representation of the output data (color format). Moreover, a resolution of 300dpi is needed for the OCR'ble portion text of the image (BW format).

- It should be noted that the sum of the sizes of the
- 30 color layer at 150dpi plus the BW layer at 300dpi is lower than the size of the color layer at 300dpi.

In this aim, according to the present invention, a method for acquiring a document based on the analysis

of the content of the document itself, comprises the following steps:

- getting an input image data;
- creating a first layer containing the image
5 information in a color format;
- creating a second layer containing the image information in a BW format;
- managing the first and the second layers in order to obtain a desired format for an output document.

10 In order to further reduce the memory area requirements, a dual path processing line 5 for the BW and color layers obtained by the dual path layer creator 1 is shown schematically in figure 11B.

15 The dual path processing line 5 comprises the dual path layer creator 1 receiving an input data 2 and outputting the first 3 and the second output data layer 4.

20 The first output data layer 3 is then processed by means of a series of a thresholder 6 and a G4 compressor 7, while the second output data layer 4 is only compressed by means of a JPEG compressor 8. The output data layer so processed are then forwarded to an output reconstruct block 9, that provide the required output format.

25 As an example, from the 300dpi 8bpp and the 150pdi 24bpp representations obtained from the dual path layer creator 1, the thresholder 6 produces a 300dpi 1bpp representation and the G4 compressor 7 a 80kByte bottom layer, while the JPEG compressor 8 produces a 250kByte
30 top layer. The effect is this of having to process only 80+250=330kByte of output data, instead of the 24MByte of input data.

As an example, creating color and BW layers, as previously suggested, decreases the memory area requirements. Moreover, elaborating layers having reduced sizes increases the elaboration speed, so
 5 enhancing the processing line's performance as a whole.

Figure 12 shows the resulting compressed layers (TEXT and IMAGE) from the dual path layer creator 1 of figure 11A.

More particularly, in order to distinguish regions on a
 10 page that are colorful from regions that are not such, a BW/color areas detection document analysis method according to the above indication comprises the following steps:

1. Analysing the input data in a Chroma space format.
- 15 2. Calculating and extracting from the input data the colorfulness of each pixel.
3. Down sampling Chroma indication channel.
4. Applying a threshold to the down sampled data.
5. Label ON the pixels having a colorfulness above
 20 the threshold and OFF the pixels having a colorfulness lower than the threshold.

According to the present invention, the BW/color areas detection document analysis method should be improved adding the further step of:

- 25 6. Grouping the color information of single small groups of pixels, improving the compression of the document and enabling the elimination of small groups of pixels that are still considered to be due to noise, or in any case, of insignificant size.

30 As shown in figure 13A, the BW/color areas detection document analysis method comprises a down sampling and

a thresholding step. Once the colorfulness of each pixel has been calculated and extracted from the input data (FORMAT 1), the image data are down sampled.

The down sampling algorithm can be performed in various ways that all have a different effect on the performance of the algorithm. If down sampling by taking the average value in a neighborhood is used, a lot of document (small regions of color due to the printing process for e.g.) and scanner noise (jitter on the RGB signal) can be eliminated.

The down sampled image data are then selected by means of a threshold, so obtaining an image having a pixels format without the spike noise (FORMAT 2). In fact, the output data are considered ON if colorfulness of the input image pixel is above the threshold and OFF if it is lower than the threshold.

The simplest case consists in applying a fixed threshold. The output of this stage is a down sampled version of the original image that has ON pixels in those regions where the color content of the original image were above the color threshold.

Different threshold values can be considered with reference to different final devices.

For example, a low resolution display does not need to receive a 16 billion color image data, since such device have no possibility of elaborating and displaying this kind of complex image data. An image data forwarded to a low resolution display can be obtained by means of particular thresholding values by limiting the number of available colors, e.g. filtering pale colors and transforming then into white or "clustering" different type of "reds" in order to have only one "red".

An example of an acceptable range for the threshold values is 0 to 30 for an input image data of 0 to 255.

The more complex case accumulates a histogram of the color content of the page and, using a heuristic,
5 decides what the best threshold for the page is.

The color information of single small groups of pixels can be further grouped together using known simple grouping techniques. The grouping step is performed on data of connected components, as shown in figure 13A
10 (FORMAT 3). This has the advantage of grouping regions of pixels that are considered colorful into bigger group. In this way, when the regions of colorful pixels are compressed (in a later stage), not every pixel has to be compressed singularly. The compression of a
15 larger group of pixels is more efficient than the singular compression of each single colorful region.

The grouping of pixels also has the advantage of enabling the elimination of small groups of pixels that are still considered to be due to noise, or in any
20 case, of insignificant size.

The whole procedure that has been depicted can also be performed on a strip basis on the whole original image, without any modification, as shown in figure 13B. Strip based analysis produces a nice side effect on the
25 grouping of pixels. In fact, if the grouping of pixels is performed on a strip basis, the grouping of pixels enables an approximation of the contour of colored regions, as shown in figure 14.

Figure 13C shows a down sampling/thresholding/grouping
30 device 10. The first component is an RGB to Chroma space converter 11. It converts, on a pixel by pixel basis, the color representation of every input pixel into a different color space representation.

When the aim is making decisions on the colorfulness of a pixel, using the right color space representation is important.

5 The RGB color space has been found not very convenient for this type of analysis. The color space used should have an indication of the colorfulness of the specific pixel. The HLN (Hue/Lightness/chroma indicator N) color space was found particularly convenient and is used in the current realization.

10 The indication of Chroma, in this HLN color space, is directly the content of the N channel, where $N = \max(R, G, B) - \min(R, G, B)$.

The down sampling/thresholding/grouping device 10 further comprises a down sampler 12, that down samples 15 the N channel, and a thresholding device 13, in turn comprising a threshold selector 14 and a look-up-table LUT 15 which apply a threshold to the down sampled data.

20 The output data is considered ON if colorfulness of the input image pixel is above the threshold and OFF if it is lower than the threshold.

Moreover, the color information of single small groups of pixels can be further grouped together by means of a grouping block 16, using known simple grouping 25 techniques on data of connected components, in order to improve the compression of the image data and eliminate small groups of pixels that are still considered to be due to noise, or in any case, of insignificant size.

30 It should be noted that a HLS to RGB converter (not shown in figure 13C) can also be added to the down sampling/thresholding/grouping device 10 in order to obtain RGB output data.

A simple grouping procedure called blobbing can be used

in order to extract the images from a document, as shown in figure 15, where the blobbed regions should correspond to the images of the document.

Moreover, after the recognition of the colorfulness content of each pixel and the blobbing of the image data, the singular images in the processed document can be separated, as shown in figure 16, by means of an AND function of such data and a mask, duly created on the basis of the following relationships:

10 RGB AND WHITE = RGB
 RGB AND BLACK = BLACK.

A data processor 17 for obtaining processed color and BW layers is shown more precisely in figure 17. The processed color and BW layers so obtained can be used, for example, in a PDF representation of the input image data. Particularly, the data processor is a scanning device 17.

The scanning device 17 has an input IN that receives the raster image data, for example in the RGB format, and is connected to a dual path layer creator component 18, which in turn outputs a first and a second layer, such layers having different data compression rate.

The first layer is inputted in a BW path 19 that outputs a processed BW layer. In a similar manner, the second layer is inputted in a color path 20 that outputs a processed color layer. The processed BW and color layers are finally inputted in a PDF device 21.

More particularly, in the example shown in figure 17, the BW path 19 comprises a threshold block 22 connected in series to a compressor 23. A G4 compression is often used in the field of BW image data processing.

Moreover, also in figure 17, the color path 20 comprises a RGB to HLN converter 24, having the output

N channel connected to a series of a down scale device 25, an histogram and threshold selector 26, a look-up-table 27, a blob analysis block 28, a fill regions block 29 and a compressor 30. A JPEG compression is
 5 often used in the field of color image data processing.

There are several advantages of the document analysis method using BW/color areas detection and scanning device according to the present invention:

1. Enables different representations of raster data
 10 be present together for different uses. An example is a 300dpi G4 compressed BW layer that lies under a 150dpi JPEG compressed color layer. The color layer is more pleasant to the eye but an OCR (Optical Characters Recognition) procedure could not be performed on the
 15 text in the JPEG layer. With this approach, the OCR may be applied to the BW data layer instead.

2. Enables a compromise between file size and use of the document itself. Taking into account the example above, a JPEG compressed 300dpi page (which can be used
 20 for OCR) will result in about 600 Kbyte. A G4 compressed 300dpi BW page will result in about 80 Kbyte but is lacking color information. If a 300dpi BW layer is overlaid with a 150dpi JPEG layer, then the resulting file size would be of about 250 Kbyte + 80
 25 Kbyte = 330 Kbyte. The resulting document would have all the characteristics of the 600dpi JPEG compressed version (OCR'able), but has half the file size.

3. In the case of selectively adding color information on the page, this approach has the
 30 advantages that, when an error is made by the algorithm and color was not added where it should have been, one always has a representation of the original data underneath (even if only BW data), and therefore no document content is lost.

4. The scanning device according to the present invention provides for an efficient way to produce this dual representation.
5. In a large series of cases, this approach achieve good compression ratios, without sacrificing the original information that is present in the document (for e.g. the extraction of text data for OCR). A layer can be added for preview, for example, without sacrificing size of the document.
- 10 6. The amount of data to process is highly reduced.